

DuraSea Rooftop Air-Cooled Air Conditioner

Drop-In Cooling Unit That Requires No Plumbing or Ducting




The DuraSea Rooftop is a 15,000 BTU/hr air conditioner* built to endure harsh marine environments. Ideal for patrol boats, house boats, and other vessels, it is designed to be installed on a flat deck or rooftop and cool the area directly below. It is air cooled and requires no plumbing or ducting.

The air-distribution box (ADB), sold separately, attaches to the underside of the unit. Accessible from the interior cabin, the ADB contains the thermostat, fan controls, return-air vent and two supply-air vents that blow in opposite directions for increased cooling capability. The three-speed blower works in cooling and ventilation-only modes.

Both the condenser and evaporator coils are coated using the ElectroFin® E-coat process which provides superior resistance to salt-air corrosion and UV damage when compared to spray coating. E-coat employs electrically charged molecules to coat the components for complete and uniform coverage with no material bridging between the fins. The E-coat material was salt-spray tested for 5,000 hours, not 1,000 like competing units. In addition, the condenser and evaporator fans are also corrosion resistant and will not rust. Unlike the competition, we use oversize coils for improved performance and dehumidification.

Rugged and strong, the DuraSea Rooftop weighs only 103 lbs. (46.7 kg). The heavy-duty reinforcement plate ties the evaporator and condenser together to minimize vibration and movement. A vibration-isolating L-bracket on the compressor and fan motor is incorporated for additional stabilization. Rubber clamps and bushings further control noise and vibration. The powder-coated base pan is 15% thicker than other models.

* The 50Hz model is rated at 12,000 BTU/hr.



Weather-tight fan motor and bearings with a stainless-steel shaft.



The air distribution box (sold separately) mounts on the ceiling to provide A/C controls.



Compressor is bracketed at top as well as bottom to minimize vibration and movement while under way.

Key Benefits

- Air-cooled unit designed for rooftop or deckmount installation.
- No plumbing or ducting required.
- Provides 15,000 BTU/hr. of cooling (60Hz model only).
- Rugged and strong, yet lightweight.
- High efficiency, low power consumption.
- ElectroFin® E-coat process for superior resistance to corrosion and UV damage.
- Vibration-free operation.
- Compressor stabilization to endure extreme motion.
- Three-speed high-performance fan for cooling and ventilation.
- Sealed motor and bearings.
- Stainless-steel fan-motor shaft.
- Oversize coils for better performance and dehumidification.
- Environmentally safe R-410A refrigerant.
- Air distribution box (sold separately) includes mechanical control and interior panel.
- Optional electric heat.


Technical Specifications for DuraSea Rooftop Air Conditioner

DuraSea Rooftop	
Model	12,000
Capacity (BTU/hr)	240V/50Hz
Capacity Cycle	7.0
Voltage/50Hz	28.0
Run Amps	R-410A
Locked Rotor Amps (LRA)	13.1/334
Refrigerant Type	29.8/759
Height (in/mm)	34.8/886
Width (in/mm)	102/46.3
Depth (in/mm)	
Net Weight (lbs/kg)	

¹ All dimensions ± 0.30 in. (8 mm).

² All weights ± 10%

Dimensions



DOMETIC MARINE DIVISION
 2000 N. Andrews Ave. | Pompano Beach, FL 33069 USA | Tel. 954-973-2477 | Fax: 954-979-4414
www.Dometic.com/Marine | MarineSales@DometicUSA.com

24/7 TECH SUPPORT FOR UNITED STATES & CANADA:
 8:00 AM to 5:00 PM Eastern Time: 800-542-2477
 After hours and weekends: 888-440-4494

INTERNATIONAL SALES & SERVICES
 Europe & the Middle East: Call +44(0)870-330-6101
 For all other areas visit our website to find your nearest distributor.

L-3010 Rev. 20130118

Specifications and availability subject to change without notice.



Dealer