

# CS Series (6K-16K) Condensers

## High-Efficiency Cooling & Heating



The CS series of condensing units for boats provides heating and cooling in a highly efficient package. The hermetically sealed, high-efficiency compressor reduces amp draw while pressure switches, thermal-overload, and start components provide constant system protection and proper operation. In addition, the expansion device and check-valve assemblies control load balancing during operation. The copper-encased cupronickel condenser coils are highly resistant to corrosion caused by continuous seawater flow.

The symmetrical base design provides optimum space efficiency and installation flexibility for easy handling and positioning of the unit. A built-in hose barb aids in complete condensate removal from the drain pan. Two sets of vibration isolators ensure quiet operation.

The electrical box can be mounted remotely. It has a moisture-resistant design with a corrosion-resistant enclosure. CS Digital (CSD) units include the Passport I/O circuit board.

As with all Marine Air products, quality is assured. Each unit is pre-charged, test-run in all operating modes, and leak-checked at the factory prior to shipping. All surface components are constructed of or coated with materials resistant to fire and corrosion. Charge Guard® protection provides sealed access ports that ensure environmental protection and system integrity. All CS condensing units meet or exceed applicable ABYC and US Coast Guard regulations, CE directives, and general Air Conditioning and Refrigeration Industry (ARI) standards.

### Key Benefits

- High-efficiency condensers.
- Valves and switches provide load balancing and constant system protection.
- Symmetrical base for installation flexibility and ease of handling.
- Electrical box can be mounted remotely.
- Passport I/O circuit board included.
- Charged, tested, and leak checked at the factory.
- Meets or exceeds all applicable standards and regulation.

# Specifications for CS Series (6K-16K) Condensers

Model <sup>(1)</sup>	CS06		CS09		CS12		CS16	
Capacity (BTU/h) <sup>(2)</sup>	6000		9000		12000		16000	
Voltage (V)	115	230	240	115	230	240	115	230
Cycle (Hz) <sup>(3)</sup> / Phase (Ph)	60/1		50/1	60/1	60/1	50/1	60/1	50/1
Full Load Amps (FLA) Cool (A)	7	3.7	4.1	6.4	3.2	4.6	9.2	4.4
Full Load Amps (FLA) Heat (A)	7.7	4	4.8	7.2	3.6	5.2	11.1	5
Locked Rotor Amps (LRA) (A) <sup>(4)</sup>	34	20	21.2	40	20	25.6	50	31
Max. Circuit Breaker (A) <sup>(5)</sup>	20	10	10	20	10	15	35	15
Min. Circuit Ampacity (A)	13	8	7	13	7	10	21	10
Refrigerant Type	417A		417A		417A		417A	
Max. Height (in/mm) <sup>(6)</sup>	15.2/387		15.2/387		15.2/387		15.2/387	
Width (in/mm) <sup>(7)</sup>	13.13/334		13.13/334		13.13/334		13.13/334	
Depth (in/mm) <sup>(7)</sup>	13.13/334		13.13/334		13.13/334		13.13/334	
Seawater Connection (in/mm)	5/16		5/16		5/16		5/16	
Refrigerant Line Connection-Discharge (in)	1/4		1/4		1/4		1/4	
Refrigerant Line Connection-Suction (in)	3/8		3/8		3/8		3/8	
Net Weight (lbs/kg) <sup>(8)</sup>	64/29.1		64/29.1		66/29.1		66/29.1	
Gross Weight (lbs/kg) <sup>(8)</sup>	74/33.6		74/33.6		75/34.1		75/34.1	

<sup>1</sup> 'D' in the model number indicates a digital control. Replace with 'M' for units with mechanical control. Add a 'Z' for 230V/60Hz units or 'Z50' for 240V/50Hz units. For example: CSD12M=115V/60Hz; CSD12KZ=230V/60Hz, CSD12KZ50=240V/50Hz

<sup>2</sup> BTU and electrical data are based on a 45°F/7.2°C evaporator and 100°F/37.8°C condenser in cool mode, and a 45°F/7.2°C evaporator and 130°F/54.4°C condenser in heat mode.

<sup>3</sup> Some 60Hz units may be operated at 50Hz but at reduced voltages that will result in a loss of capacity and higher or lower amp draw than listed. Dedicated 50Hz units are available that provide the full rated capacity, but these units must not be operated.

<sup>4</sup> Varies with voltage and load, and may be higher or lower than listed.


<sup>5</sup> Specification is for reverse-cycle units. Cool-only units may use smaller circuit breakers.

<sup>6</sup> Combined height of unit and electrical box. Subtract 2.60 in. (66 mm) for remotely-mounted electrical box. All dimensions ± 0.25 in. (6 mm).

<sup>7</sup> All dimensions ± 0.25 in. (6 mm).

<sup>8</sup> Based on 60Hz/1-phase units. All weights ± 10%

## Dimensions



### DOMETIC MARINE DIVISION

2000 N. Andrews Ave. | Pompano Beach, FL 33069 USA | Tel. 954-973-2477 | Fax: 954-979-4414  
 www.Dometic.com/Marine | MarineSales@DometicUSA.com

### 24/7 TECH SUPPORT FOR UNITED STATES & CANADA:

8:00 AM to 5:00 PM Eastern Time: 800-542-2477  
 After hours and weekends: 888-440-4494

### INTERNATIONAL SALES & SERVICES

Europe & the Middle East: Call +44(0)1870-330-6101  
 For all other areas visit our website to find your nearest distributor.

L-2-125 Rev. 20130222

Specifications and availability subject to change without notice.

Dealer

