



# AGM series



<b>AGM 12/55 (group 24)</b>	
Product code	62000550
Nominal voltage	12 V
Capacity C20*	55 Ah
CCA to DIN	300 A
CCA to SAE	480 A
Max. outer dimensions (incl. terminals and grip handles),	
lxbxh in mm/inch	257x132x207 / 10.1x5.2x8.2
Weight	17 kg / 37.5 lbs



<b>AGM 12/70 (group 27)</b>		<b>AGM 12/90 (group 31)</b>	
Product code	62000700	62000900	
Nominal voltage	12 V	12 V	
Capacity C20*	70 Ah	90 Ah	
CCA to DIN	385 A	535 A	
CCA to SAE	615 A	850 A	
Max. outer dimensions (incl. terminals and grip handles),			
lxbxh in mm/inch	348x167x183 / 13.7x6.6x7.2	330x173x237 / 13x6.8x9.3	
Weight	21 kg / 46 lbs	28 kg / 62 lbs	



<b>AGM 12/130</b>		<b>AGM 12/160 (group 4D)</b>	
Product code	62001300	62001600	
Nominal voltage	12 V	12 V	
Capacity C20*	130 Ah	160 Ah	
CCA to DIN	585 A	630 A	
CCA to SAE	935 A	1000 A	
Max. outer dimensions (incl. terminals and grip handles),			
lxbxh in mm/inch	410x177x228 / 16.1x7x9	485x170x245 / 19.1x6.7x9.6	
Weight	37.6 kg / 83 lbs	42.3 kg / 93 lbs	



<b>AGM 12/225 (group 8D)</b>		<b>AGM 12/270 (group Super 8D)</b>	
Product code	62002250	62002700	
Nominal voltage	12 V	12 V	
Capacity C20*	225 Ah	270 Ah	
CCA to DIN	815 A	1000 A	
CCA to SAE	1300 A	1600 A	
Max. outer dimensions (incl. terminals and grip handles),			
lxbxh in mm/inch	522x240x241 / 20.6x9.4x9.5	522x268x243 / 20.6x10.6x9.6	
Weight	63.5 kg / 140 lbs	73 kg / 161 lbs	

- Excellent starter function.
- Perfect upgrade for wet lead acid batteries.
- Same initial power surge in an AGM 12/90 Ah as 180 Ah wet lead-acid battery.
- Glass-fibre technology ensures low internal resistance.
- Use of thicker plates extends lifespan.
- Also for medium cyclical use.
- Two-year warranty.

\* C20 = battery capacity at a discharge time of 20 hours, till 1.75 V per cell.