





CO29

FEATURES


- 2.1 cubic feet overall refrigerator capacity maximizes storage of food and beverage items
- High output daily ice rate of up to 18 lbs and storage of up to 13 lbs of crescent ice (1/2" W \times 3/4" H \times 2-1/2" L)
- Temperature setting from 34 to 45° F provides flexibility for preserving a wide variety of items
- No drain required makes it easy and inexpensive to install and requires only a 1/4" outside diameter water line
- Conserves energy by using less electricity than a 75-watt light bulb
- Uses under 3 gallons of water to produce 25 lbs of ice
- Mechanical controlled passive cooling system
- Manual defrost maximizes ice making potential
- 220 volt model available with a 4 6 week order lead time


INTERIOR / EXTERIOR

PERFORMANCE

- Vinyl coated cabinet helps withstand tough marine environments
- Corrosion and UV resistant marine grade hardware provide better product longevity in harsh environments
- Aluminum framed door with anodized durable aluminum handle weathers outdoor elements on white model

- Field reversible door with zero clearance door swing simplifies installation
- Black model will accept a 1/4" insert panel
- No additional clearance around sides, top or rear of unit is needed for ventilation
- Sleek and contemporary look provides a very clean, high-end aesthetic
- Do not obstruct front grille air flow
- For proper installation and cut-out dimensions, see backside for details





CO29B Black Model

DIMENSIONS AND SPECIFICATIONS

OVERALL DIMENSIONS

28-1/2" (72.4) Height 20-13/16" (52.9) Width Depth 23" (58.4)

98 lbs (44 kg) Shipping weight:

Running amps 2.5 Maximum start-up amps 18.0


110/115 volt, 60 Hz Amps pertain to voltage rating Optional in 220/230 voltage, 50/60 Hz

Capacities:

Defrost technology Manual defrost 2.1 Cu. Ft Refrigerator volume Up to 18 lbs Approximate daily ice production Ice Storage Up to 13 lbs

Please visit www.u-line.com for installation guide.

All specifications are subject to change without notice.



CO29



^{*} Add 15/16" to depth for water line clearance

^{*}When installing a left-hand hinge model, allow a 145° door swing for proper removal of ice bin