

CB Series Refrigerators/Freezers

Top-Loading, Space-Saving Built-Ins



CB-036 1.3 cu. ft. unit

CB-040 1.4 cu. ft. unit

The top-loading CB Series can operate as built-in refrigerators or freezers depending on the temperature you set. Available in 1.3 cu. ft. (36 liters), 1.4 cu. ft. (39 liters), and 3.5 cu. ft. (100 liters) capacities, these units have energy-efficient Danfoss compressors that run on 12/24V DC power or 110/220V AC power (optional).

A CB unit permanently installs in a cupboard space and continues working even in inclined positions. Its lift-off lid has superior seal and insulation and can accommodate a laminate to match your countertops.



CB Series refrigerators/freezers feature a convenient space-saving design and an easy-open lid.

Key Benefits

- Permanent installation in cupboard space.
- Lid can accommodate laminate to match countertops.
- Ideal for use as a bait freezer or refrigerator.
- Stainless-steel interior housing.
- Impeccable operation in inclined positions.
- Lift-off lid with superior seal and insulation.
- Top loading for improved efficiency and better performance.
- CFC-free polyurethane insulation.
- Variable thermostat allows operation at a wide range of temperatures from refrigeration to freezing.
- Environmentally safe R-134a refrigerant.

Specification Details for CB Series Top-Loading Refrigerators/Freezers

| Model | CB-036 | CB-040 | CB-110 |
|----------------------------|--|--|--|
| Gross Capacity | 1.3 cu. ft. (36 liters) | 1.4 cu. ft. (39 liters) | 3.5 cu. ft. (100 liters) |
| Voltage | 12/24V DC 10/220V AC Optional | 12/24V DC 10/220V AC Optional | 12/24V DC 10/220V AC Optional |
| Avg. Power Consumption | 45 watts/3.75 amps | 45 watts/3.75 amps | 60 watts/3.75 amps |
| Insulation | 1.6 in. (40mm) solid polyurethane foam | 1.6 in. (40mm) solid polyurethane foam | 2.0 in. (50mm) solid polyurethane foam |
| Compressor | Danfoss BD35F | Danfoss BD35F | Danfoss BD35F |
| Refrigerant | Environmentally safe R-134A | Environmentally safe R-134A | Environmentally safe R-134A |
| Material | Zinc-coated sheet steel with stainless-steel interior; shock resistant plastic base. | Zinc-coated sheet steel with stainless-steel interior; shock resistant plastic base. | Zinc-coated sheet steel with stainless-steel interior; shock resistant plastic base. |
| Color | Gray body with dark gray lid. | Gray body with dark gray lid. | Gray body with dark gray lid. |
| Cut-Out Dimensions (WxHxD) | 16.0" x 16.0" x 23.0" ⁽¹⁾ (406mm x 406mm x 584mm ⁽¹⁾) | 13.3" x 26.0" x 19.7" (337mm x 660mm x 500mm) | 19.1" x 25.6" x 31.7" (485mm x 650mm x 805mm) |
| Net Weight | 41 lbs./18.59 kg. | 44 lbs./19.95 kg. | 62 lbs./27.9 kg. |

Notes:

⁽¹⁾ Depth is 16.0" (406mm) if the compressor is mounted remotely.



CB-110 3.5 cu. ft. unit shown

DOMETIC MARINE

2000 N. Andrews Ave. Ext. | Pompano Beach, FL 33069 USA | 954-973-2477 | Fax 954-979-4414
www.DometicUSA.com | MarineSales@DometicUSA.com

United States & Canada Tech Support

8:00 AM to 5:00 PM Eastern Time: 800-542-2477
After hours and weekends: 888-440-4494

International Sales & Service:

Europe & the Middle East: Call +44(0)870-330-6101
For all other areas visit our website to find your nearest distributor.

Dealer:



Dometic
MARINE